





P-6043



Green Pin Power Sling® Shackle BN

High load capacity, grade 8 shackle with safety bolt

- **Material:** bow and pin alloy steel, grade 8, quenched and tempered
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** ASME B30.26
- **Finish:** shackle bow painted silver, pin painted green
- **Temperature Range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^b DNV PL MPI^b US^b DNV 0377 DNV 0378 CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



working load limit	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	bearing surface	weight pin	weight each
t	b	c	d	e	f	g	h	i	j	k	l	kg	kg
125	81	165	89	134	365	220	632	382	370	36	205	17.3	97
150	95	182	90	144	390	250	703	408	420	42	248	26.1	134
200	105	204	100	154	480	276	838	446	474	47	290	35.4	196
250	120	238	110	174	540	300	938	503	513	60	314	54.8	273
300	134	260	121	189	600	350	1032	550	604	60	345	71.9	371
400	160	305	140	224	620	370	1123	635	653	70	392	114	562
500	180	340	152	255	680	450	1239	699	763	70	440	157	783
600	200	365	170	280	741	490	1354	768	818	70	475	212	1003
700	215	405	190	320	751	540	1415	849	893	70	512	271	1276
800	230	430	200	347	851	554	1547	904	917	70	536	328	1484
900	255	476	215	373	851	580	1599	963	972	70	560	426	1808
1000	270	500	232	405	851	614	1643	1030	1022	70	590	508	2132
1250	300	570	245	436	930	650	1813	1114	1144	70	670	673	2891
1550	320	590	270	469	950	680	1890	1220	1210	70	704	827	3517

CAD RFID INFO

