

TABLA DE CAPACIDADES PARA ESTROBOS MODELO "S" ALMA DE ACERO

MODELO "S" ALMA DE ACERO						
DIÁMETRO DEL CABLE		CAPACIDAD DE CARGA EN TONELADAS MÉTRICAS			LONGITUD MÍNIMA REQUERIDA EN MTS.	
PULG.	MM	VERTICAL	ENLAZADA	EN "U"		
3/8"	9.53	1.37	1.01	2.74	0.61	
7/16"	11.11	1.85	1.37	3.7	0.7	
1/2"	12.70	2.42	1.79	4.84	0.75	
9/16"	14.30	3.04	2.25	6.08	0.85	
5/8"	15.90	3.74	2.77	7.48	0.95	
3/4"	19.05	5.34	3.95	10.68	1.05	
7/8"	22.23	7.22	5.34	14.44	1.2	
1"	25.40	9.38	6.94	18.76	1.4	
1 1/8"	28.60	11.8	8.73	23.6	1.55	
1 1/4"	31.75	14.5	10.73	29	1.7	
1 3/8"	34.90	17.42	12.89	34.84	1.85	
1 1/2"	38.10	20.6	15.24	41.2	2.15	
1 3/4"	44.45	27.8	20.57	55.6	2.5	
1 7/8"	47.62	31.6	23.38	63.2	2.6	
2"	50.80	36	26.64	72	2.75	
2 1/4"	57.15	44.8	33.15	89.6	3.05	
2 1/2"	63.50	54.8	40.55	109.6	3.35	
2 3/4"	69.85	66.6	49.28	133.2	3.65	
3"	76.20	77.8	57.57	155.6	3.96	
3 1/2"	88.90	102	79	204	5.05	
4"	101.60	130	98	260	6.1	
4 1/2"	114.30	160	120	320	7.35	
6"	152.40	250	187	500	9.15	

* FACTOR DE DISEÑO DE 5:1

